



# TIMKEN BEARINGS(UK)LTD.



1222 K/C3 Bearing 2D drawings and 3D CAD models

## SKF 1222 K/C3 Self Aligning Ball Bearings

Bearing No. 1222 K/C3

Category	Self Aligning Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	5.16
EAN	7316577664037
Product Group	B00152
Mounting Method	Tapered Adapter
Enclosure	Open
Rolling Element	Ball Bearing
Adapter Sleeve	H-222
Cage Material	Steel
Precision Class	ABEC 1   ISO P0
Internal Clearance	C3-Loose
Number of Rows of Balls	Double Row
Other Features	Allowable Misalignment 3 Deg   1:12 Taper
Long Description	110MM Bore; Tapered Adapter Mount; 200MM Outside Diameter; 38MM Inner Race Width; 38MM Outer Race Width; Open; Steel Cage; Double Row of Balls; ABEC 1   ISO P0; C3-Loose
Inch - Metric	Metric
Category	Self Aligning Ball Bearings
UNSPSC	31171532
Harmonized Tariff Code	8482.10.50.68



## TIMKEN BEARINGS(UK)LTD.

Noun	Bearing
Keyword String	Self Aligning
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	1222 K/C3
Weight / LBS	11.365
D	7.874 Inch   200 Millimeter
Inner Race Width	1.496 Inch   38 Millimeter
Outer Race Width	1.496 Inch   38 Millimeter
d	4.331 Inch   110 Millimeter
bore diameter:	110 mm
static load capacity:	39 kN
outside diameter:	200 mm
precision rating:	Not Rated
overall width:	38 mm
maximum rpm:	4300 RPM
bore type:	Tapered 1:12
finish/coating:	Uncoated
closure type:	Open
outer ring width:	38 mm
internal clearance:	C3
fillet radius:	2 mm
dynamic load capacity:	88.4 kN
series:	1200